



12B

| SY Chain No. (BS) | Dimensions - mm | | | | | | | | | | | | | Average Ultimate Strength | Maximum Allowable Load | Average Chain Weight |
|-------------------|-----------------|---------|-------|------|--------|------|--------|--------|------|-----|--------------|-------|------|---------------------------|------------------------|----------------------|
| | Pitch | Bushing | | Pin | | | | Plate | | | Trans. Pitch | | | | | |
| | | Width | Dia. | Dia. | Length | | Height | Thick. | | | | | | | | |
| | P | W | R | D | LR | LC | L1 | L2 | H | T1 | T2 | T3 | TP | | | |
| 12B* | | | | | 22 | 23.6 | | | | | - | | 28.9 | 7.06 | 1.14 | 0.41 |
| 12B-2 | 19.05 | 11.68 | 12.07 | 5.72 | 41.6 | 43.1 | 11.0 | 12.6 | 16.1 | 1.8 | - | 19.46 | 57.8 | 12.0 | 2.28 | 0.78 |
| 12B-3 | | | | | 61.1 | 62.7 | | | | | - | | 86.7 | 17.6 | 3.36 | 1.18 |

* Also stocked in 100ft and 50ft reels.

16B

| SY Chain No. (BS) | Dimensions - mm | | | | | | | | | | | | | Average Ultimate Strength | Maximum Allowable Load | Average Chain Weight |
|-------------------|-----------------|---------|-------|------|--------|-------|--------|--------|------|-----|--------------|-------|-----|---------------------------|------------------------|----------------------|
| | Pitch | Bushing | | Pin | | | | Plate | | | Trans. Pitch | | | | | |
| | | Width | Dia. | Dia. | Length | | Height | Thick. | | | | | | | | |
| | P | W | R | D | LR | LC | L1 | L2 | H | T1 | T2 | T3 | TP | | | |
| 16B* | | | | | 35.1 | 38.2 | | | | | | | 60 | 16.4 | 2.59 | 0.41 |
| 16B-2 | 25.4 | 17.02 | 15.88 | 8.26 | 67.2 | 70.1 | 17.6 | 20.6 | 21.0 | 3.2 | 4.0 | 31.88 | 106 | 21.4 | 5.13 | 0.78 |
| 16B-3 | | | | | 99.2 | 102.5 | | | | | | | 160 | 31.5 | 7.68 | 1.18 |

* Also stocked in 100ft and 50ft reels.