



## 20B

SY Chain No. (BS)	Dimensions - mm												Average Ultimate Strength	Maximum Allowable Load	Average Chain Weight	
	Pitch	Bushing		Pin				Plate			Trans. Pitch					
		Width	Dia.	Dia	Length		Height	Thick.								
	P	W	R	D	LR	LC	L1	L2	H	T1	T2	T3				TP
20B					40.2	44							95	25.5	3.76	0.41
20B-2	31.75	19.56	19.05	10.16	76.8	80.6	20.1	23.9	26.4	3.5	4.5	36.45	170	33.3	7.26	0.78
20B-3					113.3	117.2							250	49.0	10.86	1.18

## 24B

SY Chain No. (BS)	Dimensions - mm												Average Ultimate Strength	Maximum Allowable Load	Average Chain Weight	
	Pitch	Bushing		Pin				Plate			Trans. Pitch					
		Width	Dia.	Dia	Length		Height	Thick.								
	P	W	R	D	LR	LC	L1	L2	H	T1	T2	T3				TP
24B					53.4	58.1							160	35.7	7.29	0.41
24B-2	38.1	25.4	25.4	14.63	101.8	106.5	26.7	31.4	33.4	4.8	5.9	48.36	280	46.8	14.53	0.78
24B-3					150.2	154.9							425	68.8	21.76	1.18