



2Pitch Offset

## 50

SY Chain No. (ANSI)	Dimensions - mm											Average Ultimate Strength Kn	Maximum Allowable Load kN	Average Chain Weight kg/m
	Pitch P	Bushing		Pin				Plate		Trans. Pitch TP				
		Width W	Dia. R	Dia. D	Length		Height H	Thick. T						
				LR	LC	L1	L2							
50*	15.875	9.53	10.16	5.08	20.4	22.0	10.2	11.8	14.6	2.0	18.1	31.9	7.22	0.98
50-2					38.4	40.0	19.2	20.8				63.8	10.7	2.00
50-3					56.7	58.2	28.4	29.8				95.7	15.7	3.07
50-4					75.0	75.7	37.5	38.2				128	20.7	3.97
50-5					93.2	94.1	46.6	47.5				160	24.5	5.02
50-6					111.4	112.5	55.7	56.8				191	28.9	6.01

\* Also stocked in 100ft and 50ft reels

## 60

SY Chain No. (ANSI)	Dimensions - mm											Average Ultimate Strength Kn	Maximum Allowable Load kN	Average Chain Weight kg/m
	Pitch P	Bushing		Pin				Plate		Trans. Pitch TP				
		Width W	Dia. R	Dia. D	Length		Height H	Thick. T						
				LR	LC	L1	L2							
60*	19.05	12.70	11.91	5.95	25.5	26.9	12.8	14.1	17.5	2.4	22.8	43.1	10.7	1.46
60-2					48.2	49.7	24	25.7				86.2	14.7	2.95
60-3					71.2	72.6	35.2	37.4				129	21.6	4.43
60-4					94.4	95.4	47.2	48.2				172	28.5	5.92
60-5					117	118.2	58.5	59.7				216	33.7	7.41
60-6					140	140.9	70.1	70.8				259	39.7	8.90
60-8					185	186.6	92.5	94.1				345	53.5	13.36
60-10					230.8	232.2	115.4	116.8				431	64.7	16.34

\* Also stocked in 100ft and 50ft reels